TRP-12OR





TRP-12OR is an excellent choice whether you are lining an irrigation pond, an industrial pond, water features in a common area, or a golf course water hazard. It is designed as a fish and plant safe liner also. TRP-12OR environmental geomembrane is a HDPE/LDPE fabric designed for economical, safe containment of contaminated soils, liquids or sludge's. It is a perfect choice for storage of remediation/treatment of contaminated materials, fuels, chemicals, and water. Being a polyethylene product it has hydrocarbon, chemical and U.V. resistance. Its cold crack characteristics are excellent at -65°F (-54°C).

(Low Temperature - Hydrocarbon Stable)

BLACK 12 x 12 COUNT PER INCH

TESTED PROPERTY	TEST METHOD		UNIT ENGLISH (METRIC)	VALUE ENGLISH (METRIC)
Thickness			mil (mm)	12 ±10% (0.30)
Weight	ASTM D 1910		oz/yd²	6.3 ± 10%
Coating Thickness			mils (mm)	2.0 ±10 % (0.05)
Tensile Strength (Grab Method)	ASTM D 751	Warp	lbs	205
		Weft	lbs	188
Elongation at Break	ASTM D 751	Warp	%	35
		Weft	%	35
Tear Strength (Tongue method)	ASTM D 751	Warp	lbs/in	59
		Weft	lbs/in	56
Bursting Strength (Mullen)	ASTM D 751		psi (kPa)	358 (2470)
Hydrostatic Resistance	ASTM D 751		psi (kPa)	104 (718)
Low Temp. Cold Crack	ASTM D 2136		°F (°C)	-65 (-54)
Moisture Vapor Transmission	ASTM E 96B		g/m²/24 hrs	0.222
Puncture Resistance	ASTM D 4833		lbs	121
Permeability	ASTM D 4491		cm/sec	0.0143
Carbon Black Content			%	2
U.V. Resistance	ASTM G-53		% retained after 2000 hrs	98

This data is provided for informational purposes only. Titan makes no warranties asto the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with us for current updates.

Toll Free: 1-866-327-1957 | Email: info@titanenviro.com | Web: www.titanenviro.com (Rev. April, 2018)