

TRP-24OR

24mil ENVIRONMENTAL GEOMEMBRANE LINER



TRP-24OR is an excellent choice whether you are lining an irrigation pond, an industrial pond, water features in a common area, or a golf course water hazard. It is designed as a fish and plant safe liner also. TRP-24OR environmental geomembrane is a HDPE/LDPE fabric designed for economical, safe containment of contaminated soils, liquids or sludge's. It is a perfect choice for storage of remediation/treatment of contaminated materials, fuels, chemicals, and water. Being a polyethylene product it has hydrocarbon, chemical and U.V. resistance. Its cold crack characteristics are excellent at -65°F (-54°C).

(Low Temperature – Hydrocarbon Stable)

1500 DENIER TAPE, BLACK 12 x 12 COUNT x2

TESTED PROPERTY	TEST METHOD		UNIT ENGLISH (METRIC)	VALUE ENGLISH (METRIC)
Thickness			mil (mm)	24 ±10% (0.60)
Weight	ASTM D 1910		oz/yd ²	12 ±5%
Coating Thickness			mils (mm)	2.0 ±10% (0.05)
Tensile Strength	ASTM D 751	Warp	lbs	449
		Weft	lbs	405
Elongation at Break	ASTM D 751	Warp	%	29
		Weft	%	34
Tear Strength (Tongue method)	ASTM D 751	Warp	lbs/in	74
		Weft	lbs/in	94
Dimensional Stability at Edge @212F/1hr	ASTM D 1204	Warp		-9.3
		Weft		-7.7
Dimensional Stability at Centre @212F/1hr	ASTM D 1204	Warp		-7.6
		Weft		-6.4
Bursting Strength (Mullen)	ASTM D 3786		psi	818
Hydrostatic Resistance	ASTM D 751A		psi	310
Puncture Resistance (1" steel ball tipped probe)	ASTM D 751		psi	642
Low Temperature Cold Crack	ASTM D 2136		°F (°C)	-65 (-54)
Moisture Vapor Transmission	ASTM E 96B		g/m ² /24 hrs	0.048
Permeability	ASTM D 4491			0.00
Flex/Abrasion	ASTM 3385		No damage to scrim after 2800 cycles, black coating worn away.	

This data is provided for informational purposes only. Titan makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with us for current updates.

TITAN ENVIRONMENTAL CONTAINMENT

Toll Free: 1-866-327-1957 | Email: info@titanenviro.com | Web: www.titanenviro.com

(Rev. April, 2018)

TRUST. QUALITY. VALUE